Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Date of issue: 11/01/1996 Revision date: 03/10/2014 Supersedes: 06/15/2011 Version: 1.0



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture

Product name : BRAKE-N-PARTS CLEANER

Product code : BRA

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Industrial and Institutional Solvent Parts Cleaner

1.3. Details of the supplier of the safety data sheet

Sky Blue Industries, Inc. 760 W. Exchange Road Ogden, Utah 84401 - USA T (800) 998-2808

1.4. Emergency telephone number

Emergency number : Chemtrec 1-800-424-9300

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GHS-US classification

Flam. Liq. 2 H225 Aquatic Acute 1 H400 Aquatic Chronic 1 H410

2.2. Label elements

GHS-US labelling

Hazard pictograms (GHS-US)



GHS09

GHS02

Signal word (GHS-US) : Danger

Hazard statements (GHS-US) : Highly flammable liquid and vapour

Very toxic to aquatic life

Very toxic to aquatic life with long lasting effects

Precautionary statements (GHS-US)

Prevention : Keep away from heat, hot surfaces, open flames, sparks. - No smoking.

Keep container tightly closed.

Ground/bond container and receiving equipment.

Use explosion-proof electrical, lighting, ventilating equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Avoid release to the environment.

Wear eye protection, protective gloves, protective clothing.

Response : IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with

water/shower.

In case of fire: Use Dry chemical, Carbon dioxide, Water spray for extinction.

Collect spillage.

Storage : Store in a well-ventilated place. Keep cool.

Disposal : Dispose of contents/container to comply with local/state/federal regulations.

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS-US)

No data available

03/12/2014 EN (English) Page 1

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 3: Composition/information on ingredients

Substance

Not applicable

Full text of H-phrases: see section 16

Mixture

| Name | Product identifier | % | GHS-US classification |
|---------------|--------------------|-----|--|
| Hexane | (CAS No) 110-54-3 | 100 | Flam. Liq. 2, H225 Aquatic Acute 1, H400 Aquatic Chronic 1, H410 |
| Mixed hexanes | N/A | | Flam. Liq. 2, H225 |

SECTION 4: First aid measures

Description of first aid measures

First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice

(show the label where possible). First-aid measures after inhalation : Assure fresh air breathing. Allow the victim to rest.

First-aid measures after skin contact Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing. Wash

contaminated clothing before reuse.

First-aid measures after eye contact Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness

First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

Most important symptoms and effects, both acute and delayed

Symptoms/injuries : Inhalation of high concentrations of this material, as could occur in enclosed spaces or during

deliberate abuse, may be associated with cardiac arrhythmias. Sympathomimetic drugs may initiate cardiac arrhythmias in persons exposed to this material. This material is an aspiration hazard. Potential danger from aspiration must be weighed against possible oral toxicity when

deciding whether to induce vomiting.

Symptoms/injuries after inhalation Irritation (nose, throat, airways). Central nervous system depression (dizziness, drowsiness,

weakness, fatigue, nausea, headache, unconsciousness).

Symptoms/injuries after ingestion : Stomach or intestinal upset (nausea, vomiting, diarrhea).

Indication of any immediate medical attention and special treatment needed 4.3.

No additional information available

SECTION 5: Firefighting measures

Extinguishing media

Suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Water spray. Sand.

: Do not use a heavy water stream. Unsuitable extinguishing media

Special hazards arising from the substance or mixture 5.2.

Fire hazard : Highly flammable liquid and vapour.

Explosion hazard : May form flammable/explosive vapour-air mixture.

Advice for firefighters

Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any

chemical fire. Avoid (reject) fire-fighting water to enter environment.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures

General measures Remove ignition sources. Use special care to avoid static electric charges. No naked lights. No

smoking.

6.1.1. For non-emergency personnel

Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection.

Emergency procedures : Ventilate area.

03/12/2014 EN (English) 2/7

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Environmental precautions

Avoid release to the environment. Prevent soil and water pollution. Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters. See Section 12 for additional Ecological information.

Methods and material for containment and cleaning up

Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect

spillage. Store away from other materials.

Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

Precautions for safe handling 7.1.

Additional hazards when processed

: Handle empty containers with care because residual vapours are flammable.

Precautions for safe handling

: Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapour. No naked lights. No smoking. Use only non-sparking tools.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures

: Proper grounding procedures to avoid static electricity should be followed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment.

Storage conditions

Keep only in the original container in a cool, well ventilated place away from: Direct sunlight, Heat sources, Combustible materials. Keep in fireproof place. Keep container tightly closed.

: Strong oxidizing agents. Strong reducing agents. Incompatible products Incompatible materials Sources of ignition. Direct sunlight. Heat sources.

Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. **Control parameters**

| Hexane (110-54-3) | | |
|-------------------|------------------|------------------------|
| USA ACGIH | ACGIH TWA (ppm) | 50 ppm |
| USA ACGIH | ACGIH STEL (ppm) | 50 ppm |
| USA ACGIH | Remark (ACGIH) | CNS impair; peripheral |

Exposure controls 8.2.

Personal protective equipment : Avoid all unnecessary exposure.

Hand protection Wear protective gloves.

Eye protection Chemical goggles or safety glasses.

Respiratory protection Wear appropriate mask.

Other information : Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

Information on basic physical and chemical properties 9.1.

Physical state : Liquid

Appearance Clear, colorless liquid

Colour Colourless Odour : Mild

Odour threshold No data available : No data available pН : No data available Relative evaporation rate (butylacetate=1) Melting point No data available : No data available Freezing point Boiling point 145 - 156 °C : -26 °C Flash point : 258 °C Auto-ignition temperature

Decomposition temperature : No data available : No data available Flammability (solid, gas)

03/12/2014 EN (English) 3/7

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Vapour pressure : No data available Relative vapour density at 20 °C : No data available Relative density : 0.67 - 0.68 Density : 5.58 - 5.63 lbs/gal Solubility : No data available Log Pow : No data available Log Kow : No data available Viscosity, kinematic : No data available Viscosity, dynamic : No data available : No data available Explosive properties Oxidising properties : No data available Explosive limits : 1.2 - 7.7 vol %

9.2. Other information

VOC content : 100 %

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Stable under normal conditions. Highly flammable liquid and vapour. May form flammable/explosive vapour-air mixture.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures. Open flame.

10.5. Incompatible materials

Strong oxidizing agents. Strong reducing agents.

10.6. Hazardous decomposition products

Hydrocarbons. Fume. Carbon monoxide. Carbon dioxide. May release flammable gases.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

| Hexane (110-54-3) | |
|---|--|
| LD50 oral rat | 25000 mg/kg (Rat) |
| LD50 dermal rabbit | 3000 mg/kg (Rabbit) |
| LC50 inhalation rat (ppm) | 48000 ppm/4h (Rat) |
| Skin corrosion/irritation | : Not classified |
| Serious eye damage/irritation | : Not classified |
| Respiratory or skin sensitisation | : Not classified |
| Germ cell mutagenicity | : Not classified |
| Carcinogenicity | : Not classified |
| Reproductive toxicity | : Not classified |
| Specific target organ toxicity (single exposure) | : Not classified |
| Specific target organ toxicity (repeated exposure) | : Not classified |
| Aspiration hazard | : Not classified |
| Potential Adverse human health effects and symptoms | : Based on available data, the classification criteria are not met. |
| Symptoms/injuries after inhalation | : Irritation (nose, throat, airways). Central nervous system depression (dizziness, drowsiness, weakness, fatigue, nausea, headache, unconsciousness). |
| Symptoms/injuries after ingestion | : Stomach or intestinal upset (nausea, vomiting, diarrhea). |

03/12/2014 EN (English) 4/7

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 12: Ecological information

12.1. Toxicity

Ecology - water : Very toxic to aquatic life with long lasting effects.

| Hexane (110-54-3) | |
|---|--|
| LC50 fishes 1 | 2.5 mg/l (96 h; Pimephales promelas) |
| EC50 Daphnia 1 | 2.1 mg/l (48 h; Daphnia magna) |
| LC50 fish 2 | 4 mg/l (24 h; Carassius auratus) |
| EC50 Daphnia 2 | 0.4 mg/l (96 h; Chaetogammarus marinus) |
| Threshold limit other aquatic organisms 1 | 9.049 mg/l (Protozoa) |
| Threshold limit algae 1 | 10 mg/l (Laminariales; Photosynthesis) |
| Threshold limit algae 2 | 26 mg/l (72 h; Pseudokirchneriella subcapitata; GLP) |

12.2. Persistence and degradability

| BRAKE-N-PARTS CLEANER | |
|--|---|
| Persistence and degradability Not established. | |
| Hexane (110-54-3) | |
| Persistence and degradability | Readily biodegradable in water. Photooxidation in water. Biodegradable in the soil. |
| ThOD | 3.52 g O ² /g substance |
| BOD (% of ThOD) | 0.63 % ThOD |

12.3. Bioaccumulative potential

| BRAKE-N-PARTS CLEANER | |
|---------------------------|-------------------------------|
| Bioaccumulative potential | Not established. |
| Hexane (110-54-3) | |
| BCF fish 1 | 501.187 (Pimephales promelas) |
| Log Pow | 3.5 - 3.94 (Calculated) |
| Bioaccumulative potential | Bioaccumable. |

12.4. Mobility in soil

| Hexane (110-54-3) | |
|-------------------|-----------|
| Surface tension | 0.018 N/m |

12.5. Other adverse effects

Other information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Dispose of

contents/container to comply with local/state/federal regulations.

Additional information : Handle empty containers with care because residual vapours are flammable.

Ecology - waste materials : Avoid release to the environment.

SECTION 14: Transport information

In accordance with DOT

Transport document description : UN1208 Hexanes, 3, II

UN-No.(DOT) : 1208
DOT NA no. : UN1208
DOT Proper Shipping Name : Hexanes

Department of Transportation (DOT) Hazard

Classes

: 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120

Hazard labels (DOT) : 3 - Flammable liquid



03/12/2014 EN (English) 5/7

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Packing group (DOT)

: II - Medium Danger

DOT Special Provisions (49 CFR 172.102) : IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite

(31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110

kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized.

T4 - 2.65 178.274(d)(2) Normal..... 178.275(d)(3)

TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = 97 / (1 + a (tr - tf)) Where: tr is the maximum mean bulk temperature

during transport, and tf is the temperature in degrees celsius of the liquid during filling.

DOT Packaging Exceptions (49 CFR 173.xxx) : 150
DOT Packaging Non Bulk (49 CFR 173.xxx) : 202
DOT Packaging Bulk (49 CFR 173.xxx) : 242
DOT Quantity Limitations Passenger aircraft/rail : 5 L
(49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 60 L

CFR 175.75)

DOT Vessel Stowage Location : E - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a

passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length, but is prohibited from carriage on passenger vessels in which the limiting number of passengers is exceeded.

Additional information

Other information : No supplementary information available.

ADR

Transport document description

Transport by sea

No additional information available

Air transport

No additional information available

SECTION 15: Regulatory information

15.1. US Federal regulations

| nexane (110-54-3) | |
|---|--|
| Listed on the United States TSCA (Toxic Substances Control Act) inventory | |
| Listed on SARA Section 313 (Specific toxic chemical listings) | |

RQ (Reportable quantity, section 304 of EPA's

List of Lists):

5000 lb

Mixed hexanes

Listed on the United States TSCA (Toxic Substances Control Act) inventory

15.2. International regulations

CANADA

No additional information available

EU-Regulations

No additional information available

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Classification according to Directive 67/548/EEC or 1999/45/EC

Not classified

15.2.2. National regulations

No additional information available

03/12/2014 EN (English) 6/7

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

15.3. US State regulations

Hexane (110-54-3)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List U.S. Pennsylvania RTK (Right to Know) List

SECTION 16: Other information

Other information : None.

Full text of H-phrases: see section 16:

| Aquatic Acute 1 | Hazardous to the aquatic environment — Acute Hazard, Category 1 |
|-------------------|---|
| Aquatic Chronic 1 | Hazardous to the aquatic environment — Chronic Hazard, Category 1 |
| Flam. Liq. 2 | Flammable liquids, Category 2 |
| H225 | Highly flammable liquid and vapour |
| H400 | Very toxic to aquatic life |
| H410 | Very toxic to aquatic life with long lasting effects |

SDS US (GHS HazCom 2012) - Custom

The information provided on this document is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

03/12/2014 EN (English) 7/7