

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Version: 1.0

Date of issue: 06/16/2008 Revision date: 06/29/2020 Supersedes: 05/14/2020

SECTION 1: Identification

1.1. Identification

Product form : Mixture

Product name : CHAMELEON ACIDIC PRESOAK

Product code : CHAAC

1.2. Recommended use and restrictions on use

Use of the substance/mixture : Industrial and Institutional Low pH Detergent

1.3. Supplier

Sky Blue Industries, Inc. 760 W. Exchange Road Ogden, Utah 84401 - USA T (800) 998-2808

www.skyblueindustries.com

1.4. Emergency telephone number

Emergency number : Chemtrec 1-800-424-9300

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Met. Corr. 1 May be corrosive to metals

Skin Corr. 1 Causes severe skin burns and eye damage

Aquatic Acute 3 Harmful to aquatic life

2.2. GHS Label elements, including precautionary statements

GHS US labeling

Hazard pictograms (GHS-US)



Signal word (GHS-US) : Danger

Hazard statements (GHS-US) : May be corrosive to metals

Causes severe skin burns and eye damage

Harmful to aquatic life

Precautionary statements (GHS-US) : Keep only in original container

Do not breathe dust/fume/gas/mist/vapors/spray

Wash hands, forearms and face thoroughly after handling

Avoid release to the environment

Wear protective gloves/protective clothing/eye protection/face protection

If swallowed: rinse mouth. Do NOT induce vomiting

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with

water/shower

If inhaled: Remove person to fresh air and keep comfortable for breathing

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing

Immediately call a poison center/doctor/... Specific treatment (see ... on this label) Wash contaminated clothing before reuse Absorb spillage to prevent material damage

Store locked up

Store in a corrosion resistant container with a resistant inner liner

Dispose of contents/container to ...

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

06/29/2020 EN (English US) Page 1

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 3: Composition/Information on ingredients

Substances

Not applicable

3.2. **Mixtures**

Name	Product identifier	%	GHS US classification
Phosphoric acid	(CAS-No.) 7664-38-2	10 – 20	Met. Corr. 1, H290 Acute Tox. 4 (Oral), H302 Skin Corr. 1B, H314
butyl glycolether	(CAS-No.) 111-76-2	3 – 5	Flam. Liq. 4, H227 Acute Tox. 4 (Oral), H302 Acute Tox. 3 (Dermal), H311 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2B, H320
Dodecyl benzene sulfonic acid	(CAS-No.) 27176-87-0	3 – 5	Acute Tox. 4 (Oral), H302 Skin Corr. 1, H314 Aquatic Acute 2, H401
UNDECETH-5	(CAS-No.) 34398-01-1	1 – 3	Skin Irrit. 2, H315 Eye Irrit. 2A, H319
Sodium xylenesulfonate	(CAS-No.) 1300-72-7	1 – 3	Skin Irrit. 2, H315 Eye Irrit. 2B, H320 STOT SE 3, H335

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. **Description of first aid measures**

First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical

advice (show the label where possible). Call a physician immediately.

First-aid measures after inhalation Remove person to fresh air and keep comfortable for breathing. Remove victim to fresh air and keep at rest in a position comfortable for breathing. Immediately call a poison center or

doctor/physician.

: Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. First-aid measures after skin contact

Immediately call a poison center or doctor/physician. Call a physician immediately.

First-aid measures after eye contact Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to

do. Continue rinsing. Immediately call a poison center or doctor/physician. Call a physician

immediately.

: Rinse mouth. Do NOT induce vomiting. Immediately call a poison center or doctor/physician. First-aid measures after ingestion

Do not induce vomiting. Call a physician immediately.

Most important symptoms and effects (acute and delayed) 4.2.

Potential Adverse human health effects and symptoms

: Based on available data, the classification criteria are not met.

Symptoms/injuries

: Causes severe skin burns and eye damage.

Symptoms/injuries after skin contact

Burns

Symptoms/injuries after eye contact

: Serious damage to eyes.

Symptoms/injuries after ingestion

: Burns

Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Water spray. Sand.

Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Specific hazards arising from the chemical

Hazardous decomposition products in case of : Toxic fumes may be released.

fire

5.3. Special protective equipment and precautions for fire-fighters

: Use water spray or fog for cooling exposed containers. Exercise caution when fighting any Firefighting instructions

chemical fire. Prevent fire-fighting water from entering environment.

06/29/2020 EN (English US) 2/12

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Protection during firefighting

: Do not enter fire area without proper protective equipment, including respiratory protection. Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures

: Ventilate spillage area. Evacuate unnecessary personnel. Keep upwind. Avoid contact with skin and eyes. Do not breathe dust/fume/gas/mist/vapors/spray. Only qualified personnel equipped with suitable protective equipment may intervene.

6.1.2. For emergency responders

Protective equipment

: Do not attempt to take action without suitable protective equipment. Equip cleanup crew with proper protection. For further information refer to section 8: "Exposure controls/personal protection".

Emergency procedures : Ventilate area.

6.2. Environmental precautions

Avoid release to the environment. Prevent entry to sewers and public waters. See Section 12 for additional Ecological information. Notify authorities if product enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment

: Dam up the liquid spill. Collect spillage.

Methods for cleaning up

Take up liquid spill into absorbent material. Neutralize spill with quicklime or soda ash. Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials. Notify authorities if product enters sewers or public waters.

Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection. For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed

: May be corrosive to metals.

Precautions for safe handling

: Ensure good ventilation of the work station. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor. Do not breathe fume/gas/mist/spray/vapours. Avoid contact during pregnancy/while nursing. Avoid contact with skin and eyes. Wear personal protective equipment. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Take all necessary technical measures to avoid or minimize the release of the product on the workplace. Limit quantities of product at the minimum necessary for handling and limit the number of exposed workers. Provide local exhaust or general room ventilation. Floors, walls and other surfaces in the hazard area must be cleaned regularly.

Hygiene measures

: Wash hands, forearms and face thoroughly after handling. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Separate working clothes from town clothes. Launder separately.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures

Packaging materials

: Comply with applicable regulations.

Storage conditions

: Keep only in the original container in a cool, well ventilated place away from : Direct sunlight, Heat sources. Keep container closed when not in use. Store in corrosive resistant container with a resistant inner liner. Keep only in original container. Store locked up. Store in a well-ventilated place. Keep cool.

ventilated place. Neep cool.

Incompatible products
Incompatible materials

Strong bases. Strong oxidizing agents.Sources of ignition. Direct sunlight. Metals.

: Store in corrosive resistant container with a resistant inner liner.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

CHAMELEON ACIDIC PRESOAK

No additional information available

06/29/2020 EN (English US) 3/12

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Phosphoric acid (7664-38-2)		
USA - ACGIH - Occupational Exposure Limits		
Local name	Phosphoric acid	
ACGIH TWA (mg/m³)	1 mg/m³	
ACGIH STEL (mg/m³)	3 mg/m³	
Remark (ACGIH)	URT, eye, & skin irr	
USA - OSHA - Occupational Exposure Limits		
Local name	Phosphoric acid	
OSHA PEL (TWA) (mg/m³)	1 mg/m³	
Dodecyl benzene sulfonic acid (27176-87-0)		
No additional information available		
UNDECETH-5 (34398-01-1)		
No additional information available		
butyl glycolether (111-76-2)		
USA - ACGIH - Occupational Exposure Limits		
Local name	2-Butoxyethanol (EGBE)	
ACGIH TWA (ppm)	20 ppm	
Remark (ACGIH)	Eye & URT irr	
USA - OSHA - Occupational Exposure Limits		
Local name	2-Butoxyethanol	
OSHA PEL (TWA) (mg/m³)	240 mg/m³	
OSHA PEL (TWA) (ppm)	50 ppm	
Sodium xylenesulfonate (1300-72-7)		
No additional information available		

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.

Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Avoid all unnecessary exposure.

Hand protection:

Wear protective gloves

Eye protection:

Chemical goggles or face shield. Safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

Wear appropriate mask. Wear respiratory protection

Personal protective equipment symbol(s):



Other information:

Do not eat, drink or smoke during use.

06/29/2020 EN (English US) 4/12

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid Color : Purple

Odor : Slight detergent
Odor threshold : No data available

pH : <2 pH solution : 1%

Melting point: Not applicableFreezing point: No data availableBoiling point: No data available

Flash point : > 212 °F

Relative evaporation rate (butyl acetate=1) : No data available Flammability (solid, gas) : Non flammable. Vapor pressure : No data available Relative vapor density at 20 °C : No data available

Relative density : 1.10 Specific gravity / density 9.15 lb/gal Solubility : Soluble in water. Partition coefficient n-octanol/water (Log Pow) : No data available Auto-ignition temperature : No data available Decomposition temperature : No data available Viscosity, kinematic No data available : No data available Viscosity, dynamic **Explosion limits** : No data available Explosive properties : No data available : No data available Oxidizing properties

9.2. Other information

VOC content : 7 %

SECTION 10: Stability and reactivity

10.1. Reactivity

Reacts violently with (strong) bases. Thermal decomposition generates: Corrosive vapors.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures.

10.5. Incompatible materials

Strong bases. Strong oxidizing agents. May be corrosive to metals. metals.

10.6. Hazardous decomposition products

Fume. Carbon monoxide. Carbon dioxide. Thermal decomposition generates : Corrosive vapors.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

06/29/2020 EN (English US) 5/12

Safety Data Sheet

Sodium xylenesulfonate (1300-72-7)

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Phosphoric acid (7664-38-2)	
LD50 oral rat	1530 mg/kg (85 % aqueous solution; Rat; Equivalent or similar to OECD 423; Literature study; 2600 mg/kg bodyweight; 80 % aqueous solution; Rat; Experimental value; 3500 mg/kg bodyweight; 75 % aqueous solution; Rat; Experimental value; 4200 mg/kg bodyweight; Rat; Experimental value; 4400 mg/kg bodyweight; Rat; Experimental value)
LD50 dermal rabbit	2740 mg/kg body weight (85 % aqueous solution; Rabbit; Experimental value; >1260 mg/kg bodyweight; 80 % aqueous solution; Rabbit; Experimental value; >3160 mg/kg bodyweight; 75 % aqueous solution; Rabbit; Experimental value; >3160 mg/kg bodyweight; Rabbit; Experimental value)
Dodecyl benzene sulfonic acid (27176-87-0	
LD50 oral rat	1080 mg/kg body weight (OECD 401: Acute Oral Toxicity, Rat, Male / female, Read-across, Oral, 14 day(s))
LD50 dermal rat	> 2000 mg/kg body weight (OECD 402: Acute Dermal Toxicity, 24 h, Rat, Male / female, Read-across, Dermal, 14 day(s))
LC50 inhalation rat (mg/l)	0.31 mg/l air (4 h, Rat, Male, Read-across, Inhalation (aerosol), 14 day(s))
UNDECETH-5 (34398-01-1)	
LD50 oral rat	> 1400 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
butyl glycolether (111-76-2)	
LD50 oral rat	1746 mg/kg body weight (Equivalent or similar to OECD 401, Rat, Male, Experimental value, Oral)
LD50 dermal rat	> 2000 mg/kg body weight (Rat; Experimental value; OECD 402: Acute Dermal Toxicity)
LD50 dermal rabbit	435 mg/kg body weight (Rabbit; Experimental value; OECD 402: Acute Dermal Toxicity; 435 mg/kg bodyweight; Rabbit; Weight of evidence; Equivalent or similar to OECD 402)
LC50 inhalation rat (ppm)	450-486,Rat; Weight of evidence
Sodium xylenesulfonate (1300-72-7)	
LD50 oral rat	> 7000 mg/kg body weight (OECD 401: Acute Oral Toxicity, Rat, Male / female, Read-across, Oral, 14 day(s))
LD50 dermal rabbit	> 2000 mg/kg body weight (Equivalent or similar to OECD 402, Rabbit, Read-across, Dermal, 14 day(s))
Skin corrosion/irritation	: Causes severe skin burns. pH: < 2
Serious eye damage/irritation	: Assumed to cause serious eye damage pH: < 2
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
Specific target organ toxicity – single exposure	: Not classified

Symptoms/injuries after skin contact	: Burns.
Communication of the solution	Direct
Symptoms/injuries	: Causes severe skin burns and eye damage.
Potential Adverse human health effects and symptoms	: Based on available data, the classification criteria are not met.
Likely routes of exposure	: Skin and eye contact. Inhalation.
Viscosity, kinematic	: No data available
Aspiration hazard	. Not classified
Assiration bazard	: Not classified
exposure	. Not oldosilled
Specific target organ toxicity – repeated	: Not classified
Specific target organ toxicity – single exposure	May cause respiratory irritation.

06/29/2020 EN (English US) 6/12

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Symptoms/injuries after eye contact : Serious damage to eyes.

Symptoms/injuries after ingestion : Burns.

SECTION 12: Ecological information

12.1			itv

Ecology - general : Harmful to aquatic life.
Ecology - water : Harmful to aquatic life.

Phosphoric acid (7664-38-2)		
LC50 fish 1	138 mg/l (96 h; Pisces; Pure substance)	
LC50 other aquatic organisms 1	100-1000,96 h; Protozoa; Pure substance	
EC50 Daphnia 1	> 100 mg/l (48 h; Daphnia magna; Pure substance)	
LC50 fish 2	100 – 1000 mg/l (Pisces; Pure substance)	
LC50 other aquatic organisms 2	240 mg/l (96 h; Pure substance)	
TLM fish 1	138 ppm (96 h; Gambusia affinis; Pure substance)	
Threshold limit other aquatic organisms 1	100-1000,96 h; Protozoa; Pure substance	
Threshold limit other aquatic organisms 2	240 mg/l (96 h; Pure substance)	
Threshold limit algae 1	> 100 mg/l (72 h; Desmodesmus subspicatus; Pure substance)	
Threshold limit algae 2	100 mg/l (72 h; Desmodesmus subspicatus; Pure substance)	

Dodecyl benzene sulfonic acid (27176-87-0)	
LC50 fish 1	4.1 mg/l (DIN 38412-15, 96 h, Leuciscus idus, Static system, Fresh water, Experimental value, Nominal concentration)
EC50 Daphnia 1	2.5 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Nominal concentration)
ErC50 (algae)	65.4 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value)

UNDECETH-5 (34398-01-1)	
LC50 fish 1	1 – 10 mg/l (96 hr.)
EC50 Daphnia 1	1 – 10 mg/l (48 hr.)
EC50 other aquatic organisms 1	1 – 10 mg/l (96 hr.)(Algae)

butyl glycolether (111-76-2)	
LC50 fish 1	1474 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Oncorhynchus mykiss, Static system, Fresh water, Experimental value, Nominal concentration)
EC50 Daphnia 1	1550 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, Nominal concentration)
ErC50 (algae)	911 mg/l (72 Hr.)

Sodium xylenesulfonate (1300-72-7)	
LC50 fish 1	> 1000 mg/l (EPA OTS 797.1400, 96 h, Oncorhynchus mykiss, Static system, Fresh water, Experimental value)
EC50 Daphnia 1	> 1000 mg/l (EPA OTS 797.1300, 48 h, Daphnia magna, Static system, Fresh water, Experimental value)

12.2. Persistence and degradability

CHAMELEON ACIDIC PRESOAK		
Persistence and degradability	Not established.	
Phosphoric acid (7664-38-2)		
Persistence and degradability	Biodegradability: not applicable. No (test)data on mobility of the substance available.	
ThOD	Not applicable	
Dodecyl benzene sulfonic acid (27176-87-0)		
Persistence and degradability	Readily biodegradable in water.	
Chemical oxygen demand (COD)	2.41 g O₂/g substance	
butyl glycolether (111-76-2)		
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. Photodegradation in the air.	
Biochemical oxygen demand (BOD)	0.71 g O₂/g substance	

06/29/2020 EN (English US) 7/12

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

butyl glycolether (111-76-2)	
Chemical oxygen demand (COD)	2.2 g O₂/g substance
ThOD	2.305 g O₂/g substance
BOD (% of ThOD)	0.31
Sodium xylenesulfonate (1300-72-7)	
Persistence and degradability	Readily biodegradable in water.

12.3. Bioaccumulative potential

CHAMELEON ACIDIC PRESOAK		
	Not established.	
Bioaccumulative potential	Not established.	
Phosphoric acid (7664-38-2)		
Bioaccumulative potential	Not bioaccumulative.	
Dodecyl benzene sulfonic acid (27176-87-0)		
BCF fish 1	65 – 96 (OECD 305: Bioconcentration: Flow-Through Fish Test, 32 day(s), Pimephales promelas, Static system, Fresh water, Experimental value, Fresh weight)	
Partition coefficient n-octanol/water (Log Pow)	1.96 (Weight of evidence approach, Equivalent or similar to OECD 107, 25 °C)	
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).	
butyl glycolether (111-76-2)		
Partition coefficient n-octanol/water (Log Pow)	0.81 (Experimental value; BASF test; 25 °C)	
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).	
Sodium xylenesulfonate (1300-72-7)		
Partition coefficient n-octanol/water (Log Pow)	-3.12 (Experimental value, EU Method A.8: Partition Coefficient, 20 °C)	
Bioaccumulative potential	Not bioaccumulative.	

12.4. Mobility in soil

Dodecyl benzene sulfonic acid (27176-87-0)	
Surface tension	29.3 – 31.8 N/m (25 °C, 120 mg/l)
Partition coefficient n-octanol/water (Log Koc)	3.96 (log Koc, OECD 106: Adsorption/Desorption Using a Batch Equilibrium Method, Calculated value)
Ecology - soil	Low potential for mobility in soil.
butyl glycolether (111-76-2)	
Surface tension	0.027 N/m (25 °C)
Ecology - soil	Low potential for adsorption in soil.
Sodium xylenesulfonate (1300-72-7)	
Surface tension	71 mN/m (20 °C, 90 %, EU Method A.5: Surface tension)
Ecology - soil	No (test)data on mobility of the substance available.

12.5. Other adverse effects

Other information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Disposal methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Dispose of

contents/container to comply with local/state/federal regulations.

Ecology - waste materials : Avoid release to the environment.

06/29/2020 EN (English US) 8/12

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Transport document description : UN3264 Corrosive liquid, acidic, inorganic, n.o.s. (Phosphoric acid), 8, III

UN-No.(DOT) : UN3264

Proper Shipping Name (DOT) : Corrosive liquid, acidic, inorganic, n.o.s.

Phosphoric acid

Class (DOT) : 8 - Class 8 - Corrosive material 49 CFR 173.136

Packing group (DOT) : III - Minor Danger Hazard labels (DOT) : 8 - Corrosive



DOT Packaging Non Bulk (49 CFR 173.xxx) : 203 DOT Packaging Bulk (49 CFR 173.xxx) : 241

DOT Symbols : G - Identifies PSN requiring a technical name

DOT Symbols

1. G - Identifies F3N requiring a technical frame

DOT Special Provisions (49 CFR 172.102)

2. IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid pl

: IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672).

T7 - 4 178.274(d)(2) Normal..... 178.275(d)(3)

TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = 97 / 1 + a (tr - tf) Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling. TP28 - A portable tank having a minimum test pressure of 2.65 bar (265 kPa) may be used provided the calculated test pressure is 2.65 bar or less based on the MAWP of the hazardous material, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the

MAWP.

DOT Packaging Exceptions (49 CFR 173.xxx) : 154
DOT Quantity Limitations Passenger aircraft/rail : 5 L

(49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 60 L

CFR 175.75)

DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a

passenger vessel.

DOT Vessel Stowage Other : 40 - Stow "clear of living quarters"
Other information : No supplementary information available.

Transportation of Dangerous Goods

Not applicable

Transport by sea

Not applicable

Air transport

Not applicable

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory except for:

Liquitint Brilliant Orange (L82000)	CAS-No.	1 – 3%
-------------------------------------	---------	--------

06/29/2020 EN (English US) 9/12

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

		<u> </u>	
Contains chemical(s) subject to TSCA 12b expor	t notification if pro	1	
Acetaldehyde		CAS-No. 75-07-0	< 0.1%
Chemical(s) subject to the reporting requirements 1986 and 40 CFR Part 372.	s of Section 313 or	Title III of the Superfund Ame	endments and Reauthorization Act (SARA) of
Sulfuric acid		CAS-No. 7664-93-9	< 1%
Ethylene oxide		CAS-No. 75-21-8	< 0.1%
Acetaldehyde		CAS-No. 75-07-0	< 0.1%
1,4-dioxane		CAS-No. 123-91-1	< 0.1%
Methyl alcohol		CAS-No. 67-56-1	< 0.1%
ethylene glycol		CAS-No. 107-21-1	< 0.1%
Phosphoric acid (7664-38-2)			
CERCLA RQ	5000 lb		
Dodecyl benzene sulfonic acid (27176-87-0)			
CERCLA RQ	1000 lb		
Sulfuric acid (7664-93-9)			
CERCLA RQ	1000 lb		
RQ (Reportable quantity, section 304 of EPA's	1000 lb		
List of Lists)			
SARA Section 302 Threshold Planning Quantity (TPQ)	1000 lb		
Sulfer dioxide (7446-09-5)			
RQ (Reportable quantity, section 304 of EPA's List of Lists)	500 lb		
SARA Section 302 Threshold Planning Quantity (TPQ)	500 lb		
UNDECETH-5 (34398-01-1)			
EPA TSCA Regulatory Flag	name but is con regardless of the P - P - indicates XU - XU - indica	sidered to cover the designate e amount used. a commenced PMN substanc tes a substance exempt from i	ning no free-radical initiator in its Inventory d polymer made with any free-radical initiator e. e. reporting under the Inventory Update Reporting pata Base Production and Site Reports (40)
SARA Section 311/312 Hazard Classes	Immediate (acut	e) health hazard	
Ethylene oxide (75-21-8)			
Listed on EPA Hazardous Air Pollutant (HAPS)			
CERCLA RQ	10 lb		
RQ (Reportable quantity, section 304 of EPA's List of Lists)	10 lb		
SARA Section 302 Threshold Planning Quantity (TPQ)	1000 lb		
Acetaldehyde (75-07-0)			
Listed on EPA Hazardous Air Pollutant (HAPS)			
EPA TSCA Regulatory Flag	T - T - indicates	a substance that is the subjec	t of a Section 4 test rule under TSCA.
CERCLA RQ	1000 lb		
1,4-dioxane (123-91-1)			
Listed on EPA Hazardous Air Pollutant (HAPS)			
CERCLA RQ	100 lb		
Methyl alcohol (67-56-1)			
Listed on EPA Hazardous Air Pollutant (HAPS)			
CERCLA RQ	5000 lb		
butyl glycolether (111-76-2)			
SARA Section 311/312 Hazard Classes	Fire hazard Immediate (acut Delayed (chroni	re) health hazard c) health hazard	

06/29/2020 EN (English US) 10/12

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

ethylene glycol (107-21-1)	
Listed on EPA Hazardous Air Pollutant (HAPS)	
CERCLA RQ	5000 lb

15.2. International regulations

Sulfuric acid (7664-93-9)

Listed as carcinogen on NTP (National Toxicology Program)

Ethylene oxide (75-21-8)

Listed on IARC (International Agency for Research on Cancer) Listed as carcinogen on NTP (National Toxicology Program)

Acetaldehyde (75-07-0)

Listed as carcinogen on NTP (National Toxicology Program)

1,4-dioxane (123-91-1)

Listed on IARC (International Agency for Research on Cancer) Listed as carcinogen on NTP (National Toxicology Program)

15.3. US State regulations



This product can expose you to Ethylene oxide, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Component	State or local regulations
Phosphoric acid(7664-38-2)	U.S New Jersey - Right to Know Hazardous Substance List; U.S Pennsylvania - RTK (Right to Know) List
Glycerol(56-81-5)	U.S New Jersey - Right to Know Hazardous Substance List
butyl glycolether(111-76-2)	U.S New Jersey - Right to Know Hazardous Substance List
ethylene glycol(107-21-1)	U.S New Jersey - Right to Know Hazardous Substance List
1,4-dioxane(123-91-1)	U.S New Jersey - Right to Know Hazardous Substance List
Ethylene oxide(75-21-8)	U.S New Jersey - Right to Know Hazardous Substance List
Methyl alcohol(67-56-1)	U.S New Jersey - Right to Know Hazardous Substance List
Acetaldehyde(75-07-0)	U.S New Jersey - Right to Know Hazardous Substance List
Dodecyl benzene sulfonic acid(27176-87-0)	U.S New Jersey - Right to Know Hazardous Substance List
Sulfuric acid(7664-93-9)	U.S New Jersey - Right to Know Hazardous Substance List
Sulfer dioxide(7446-09-5)	U.S New Jersey - Right to Know Hazardous Substance List

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date : 06/29/2020 Other information : None.

06/29/2020 EN (English US) 11/12

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full text of H-phrases:

Acute Tox. 3 (Dermal) Acute toxicity (dermal) Category 3 Acute Tox. 4 (Inhalation) Acute toxicity (inhalation) Category 4 Acute Tox. 4 (Oral) Acute toxicity (oral) Category 4 Aquatic Acute 2 Hazardous to the aquatic environment - Acute Hazard Category 2 Aquatic Acute 3 Hazardous to the aquatic environment - Acute Hazard Category 3 Eye Irrit. 2A Serious eye damage/eye irritation Category 2A Eye Irrit. 2B Serious eye damage/eye irritation Category 2B Flam. Liq. 4 Flammable liquids Category 4 Met. Corr. 1 Corrosive to metals Category 1 Skin Corr. 1 Skin corrosion/irritation Category 1 Skin Corr. 1 Skin corrosion/irritation Category 1 Skin Irrit. 2 Skin corrosion/irritation Category 2 STOT SE 3 Specific target organ toxicity (single exposure) Category 3 H227 Combustible liquid H290 May be corrosive to metals H302 Harmful if swallowed H311 Toxic in contact with skin H314 Causes severe skin burns and eye damage H315 Causes sevin seyi irritation H320 Causes serious eye irritation H332 Harmful if inhaled H335 May cause respiratory irritation H336 May cause respiratory irritation H401 Toxic to aquatic life		
Acute Tox. 4 (Oral) Acute toxicity (oral) Category 4 Aquatic Acute 2 Hazardous to the aquatic environment - Acute Hazard Category 2 Aquatic Acute 3 Hazardous to the aquatic environment - Acute Hazard Category 3 Eye Irrit. 2A Serious eye damage/eye irritation Category 2A Eye Irrit. 2B Serious eye damage/eye irritation Category 2B Flam. Liq. 4 Flammable liquids Category 4 Met. Corr. 1 Corrosive to metals Category 1 Skin Corr. 1 Skin corrosion/irritation Category 1 Skin Corr. 1B Skin corrosion/irritation Category 1B Skin Irrit. 2 Skin corrosion/irritation Category 2 STOT SE 3 Specific target organ toxicity (single exposure) Category 3 H227 Combustible liquid H290 May be corrosive to metals H302 Harmful if swallowed H311 Toxic in contact with skin H314 Causes severe skin burns and eye damage H315 Causes skin irritation H320 Causes eye irritation H332 Harmful if inhaled H335 May cause respiratory irritation	Acute Tox. 3 (Dermal)	Acute toxicity (dermal) Category 3
Aquatic Acute 2 Hazardous to the aquatic environment - Acute Hazard Category 2 Aquatic Acute 3 Hazardous to the aquatic environment - Acute Hazard Category 3 Eye Irrit. 2A Serious eye damage/eye irritation Category 2A Eye Irrit. 2B Serious eye damage/eye irritation Category 2B Flam. Liq. 4 Flammable liquids Category 4 Met. Corr. 1 Corrosive to metals Category 1 Skin Corr. 1 Skin corrosion/irritation Category 1 Skin Corr. 1 Skin corrosion/irritation Category 1B Skin Irrit. 2 Skin corrosion/irritation Category 2 STOT SE 3 Specific target organ toxicity (single exposure) Category 3 H227 Combustible liquid H290 May be corrosive to metals H302 Harmful if swallowed H311 Toxic in contact with skin H314 Causes severe skin burns and eye damage H315 Causes skin irritation H319 Causes serious eye irritation H320 Causes eye irritation H332 Harmful if inhaled H335 May cause respiratory irritation	Acute Tox. 4 (Inhalation)	Acute toxicity (inhalation) Category 4
Aquatic Acute 3 Hazardous to the aquatic environment - Acute Hazard Category 3 Eye Irrit. 2A Serious eye damage/eye irritation Category 2A Eye Irrit. 2B Serious eye damage/eye irritation Category 2B Flam. Liq. 4 Flammable liquids Category 4 Met. Corr. 1 Corrosive to metals Category 1 Skin Corr. 1 Skin corrosion/irritation Category 1 Skin Corr. 1B Skin corrosion/irritation Category 1B Skin Irrit. 2 Skin corrosion/irritation Category 2 STOT SE 3 Specific target organ toxicity (single exposure) Category 3 H227 Combustible liquid H290 May be corrosive to metals H302 Harmful if swallowed H311 Toxic in contact with skin H314 Causes severe skin burns and eye damage H315 Causes skin irritation H319 Causes serious eye irritation H320 Causes eye irritation H332 Harmful if inhaled H335 May cause respiratory irritation	Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4
Eye Irrit. 2A Serious eye damage/eye irritation Category 2A Eye Irrit. 2B Serious eye damage/eye irritation Category 2B Flam. Liq. 4 Flammable liquids Category 4 Met. Corr. 1 Corrosive to metals Category 1 Skin Corr. 1 Skin corrosion/irritation Category 1 Skin Corr. 1B Skin corrosion/irritation Category 1B Skin Irrit. 2 Skin corrosion/irritation Category 2 STOT SE 3 Specific target organ toxicity (single exposure) Category 3 H227 Combustible liquid H290 May be corrosive to metals H302 Harmful if swallowed H311 Toxic in contact with skin H314 Causes severe skin burns and eye damage H315 Causes skin irritation H319 Causes serious eye irritation H320 Causes eye irritation H332 Harmful if inhaled H335 May cause respiratory irritation	Aquatic Acute 2	Hazardous to the aquatic environment - Acute Hazard Category 2
Eye Irrit. 2B Serious eye damage/eye irritation Category 2B Flam. Liq. 4 Flammable liquids Category 4 Met. Corr. 1 Corrosive to metals Category 1 Skin Corr. 1 Skin corrosion/irritation Category 1 Skin Corr. 1B Skin corrosion/irritation Category 1B Skin lrrit. 2 Skin corrosion/irritation Category 2 STOT SE 3 Specific target organ toxicity (single exposure) Category 3 H227 Combustible liquid H290 May be corrosive to metals H302 Harmful if swallowed H311 Toxic in contact with skin H314 Causes severe skin burns and eye damage H315 Causes skin irritation H319 Causes serious eye irritation H320 Causes eye irritation H332 Harmful if inhaled H335 May cause respiratory irritation	Aquatic Acute 3	Hazardous to the aquatic environment - Acute Hazard Category 3
Flam. Liq. 4 Flammable liquids Category 4 Met. Corr. 1 Corrosive to metals Category 1 Skin Corr. 1 Skin corrosion/irritation Category 1 Skin Corr. 1B Skin corrosion/irritation Category 1B Skin Irrit. 2 Skin corrosion/irritation Category 2 STOT SE 3 Specific target organ toxicity (single exposure) Category 3 H227 Combustible liquid H290 May be corrosive to metals H302 Harmful if swallowed H311 Toxic in contact with skin H314 Causes severe skin burns and eye damage H315 Causes skin irritation H319 Causes serious eye irritation H320 Causes eye irritation H332 Harmful if inhaled H335 May cause respiratory irritation	Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Met. Corr. 1Corrosive to metals Category 1Skin Corr. 1Skin corrosion/irritation Category 1Skin Corr. 1BSkin corrosion/irritation Category 1BSkin Irrit. 2Skin corrosion/irritation Category 2STOT SE 3Specific target organ toxicity (single exposure) Category 3H227Combustible liquidH290May be corrosive to metalsH302Harmful if swallowedH311Toxic in contact with skinH314Causes severe skin burns and eye damageH315Causes skin irritationH319Causes serious eye irritationH320Causes eye irritationH332Harmful if inhaledH335May cause respiratory irritation	Eye Irrit. 2B	Serious eye damage/eye irritation Category 2B
Skin Corr. 1 Skin Corr. 1B Skin corrosion/irritation Category 1B Skin Irrit. 2 Skin corrosion/irritation Category 2 STOT SE 3 Specific target organ toxicity (single exposure) Category 3 H227 Combustible liquid H290 May be corrosive to metals H302 Harmful if swallowed H311 Toxic in contact with skin Causes severe skin burns and eye damage H315 Causes skin irritation H319 Causes serious eye irritation H320 Causes eye irritation H332 Harmful if inhaled H335 May cause respiratory irritation	Flam. Liq. 4	Flammable liquids Category 4
Skin Corr. 1B Skin corrosion/irritation Category 1B Skin Irrit. 2 Skin corrosion/irritation Category 2 STOT SE 3 Specific target organ toxicity (single exposure) Category 3 H227 Combustible liquid H290 May be corrosive to metals H302 Harmful if swallowed H311 Toxic in contact with skin H314 Causes severe skin burns and eye damage H315 Causes skin irritation H319 Causes serious eye irritation H320 Causes eye irritation H332 Harmful if inhaled H335 May cause respiratory irritation	Met. Corr. 1	Corrosive to metals Category 1
Skin Irrit. 2 Skin corrosion/irritation Category 2 STOT SE 3 Specific target organ toxicity (single exposure) Category 3 H227 Combustible liquid H290 May be corrosive to metals H302 Harmful if swallowed H311 Toxic in contact with skin H314 Causes severe skin burns and eye damage H315 Causes skin irritation H319 Causes serious eye irritation H320 Causes eye irritation H332 Harmful if inhaled H335 May cause respiratory irritation	Skin Corr. 1	Skin corrosion/irritation Category 1
STOT SE 3 Specific target organ toxicity (single exposure) Category 3 H227 Combustible liquid H290 May be corrosive to metals H302 Harmful if swallowed H311 Toxic in contact with skin H314 Causes severe skin burns and eye damage H315 Causes skin irritation H319 Causes serious eye irritation H320 Causes eye irritation H332 Harmful if inhaled H335 May cause respiratory irritation	Skin Corr. 1B	Skin corrosion/irritation Category 1B
H227 Combustible liquid H290 May be corrosive to metals H302 Harmful if swallowed H311 Toxic in contact with skin H314 Causes severe skin burns and eye damage H315 Causes skin irritation H319 Causes serious eye irritation H320 Causes eye irritation H332 Harmful if inhaled H335 May cause respiratory irritation	Skin Irrit. 2	Skin corrosion/irritation Category 2
H290May be corrosive to metalsH302Harmful if swallowedH311Toxic in contact with skinH314Causes severe skin burns and eye damageH315Causes skin irritationH319Causes serious eye irritationH320Causes eye irritationH332Harmful if inhaledH335May cause respiratory irritation	STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H302 Harmful if swallowed H311 Toxic in contact with skin H314 Causes severe skin burns and eye damage H315 Causes skin irritation H319 Causes serious eye irritation H320 Causes eye irritation H332 Harmful if inhaled H335 May cause respiratory irritation	H227	Combustible liquid
H311 Toxic in contact with skin H314 Causes severe skin burns and eye damage H315 Causes skin irritation H319 Causes serious eye irritation H320 Causes eye irritation H332 Harmful if inhaled H335 May cause respiratory irritation	H290	May be corrosive to metals
H314 Causes severe skin burns and eye damage H315 Causes skin irritation H319 Causes serious eye irritation H320 Causes eye irritation H332 Harmful if inhaled H335 May cause respiratory irritation	H302	Harmful if swallowed
H315 Causes skin irritation H319 Causes serious eye irritation H320 Causes eye irritation H332 Harmful if inhaled H335 May cause respiratory irritation	H311	Toxic in contact with skin
H319 Causes serious eye irritation H320 Causes eye irritation H332 Harmful if inhaled H335 May cause respiratory irritation	H314	Causes severe skin burns and eye damage
H320 Causes eye irritation H332 Harmful if inhaled H335 May cause respiratory irritation	H315	Causes skin irritation
H332 Harmful if inhaled H335 May cause respiratory irritation	H319	Causes serious eye irritation
H335 May cause respiratory irritation	H320	Causes eye irritation
	H332	Harmful if inhaled
H401 Toxic to aquatic life	H335	May cause respiratory irritation
	H401	Toxic to aquatic life

SDS US (GHS HazCom 2012)

The information provided on this document is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

06/29/2020 EN (English US) 12/12