

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Date of issue: 11/01/1997 Revision date: 05/27/2020 Supersedes: 03/31/2014

Version: 1.0

SECTION 1: Identification

1.1. Identification

Product form : Mixture
Product name : PREVAIL
Product code : PREV

1.2. Recommended use and restrictions on use

Use of the substance/mixture : Industrial and Institutional Alkaline Detergent/Degreaser

1.3. Supplier

Sky Blue Industries, Inc. 760 W. Exchange Road Ogden, Utah 84401 - USA T (800) 998-2808

www.skyblueindustries.com

1.4. Emergency telephone number

Emergency number : Chemtrec 1-800-424-9300

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Skin Irrit. 2 Causes skin irritation
Eye Dam. 1 Causes serious eye damage

2.2. GHS Label elements, including precautionary statements

GHS US labeling

Hazard pictograms (GHS-US)



Signal word (GHS-US) : Danger

Hazard statements (GHS-US) : Causes skin irritation

Causes serious eye damage

Precautionary statements (GHS-US) : Wash hands, forearms and face thoroughly after handling

Wear protective gloves/protective clothing/eye protection/face protection

If on skin: Wash with plenty of water/...

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing Immediately call a poison center/doctor/... Specific treatment (see ... on this label)

If skin irritation occurs: Get medical advice/attention Take off contaminated clothing and wash it before reuse

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

05/27/2020 EN (English US) Page 1

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Name	Product identifier	%	GHS US classification
Ethanolamine	(CAS-No.) 141-43-5	1 – 5	Flam. Liq. 4, H227 Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Inhalation), H332 Skin Corr. 1, H314 Aquatic Acute 3, H402
butyl glycolether	(CAS-No.) 111-76-2	1-3	Flam. Liq. 4, H227 Acute Tox. 4 (Oral), H302 Acute Tox. 3 (Dermal), H311 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2B, H320
UNDECETH-5	(CAS-No.) 34398-01-1	1 – 3	Skin Irrit. 2, H315 Eye Irrit. 2A, H319
Tetrasodium ethylenediaminetetraactetate	(CAS-No.) 64-02-8	0.1 – 3	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Inhalation:dust,mist), H332 Eye Dam. 1, H318

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. Allow victim to breathe fresh

air. Allow the victim to rest.

First-aid measures after skin contact : Wash with plenty of soap and water. Wash contaminated clothing before reuse. If skin irritation

occurs: Get medical advice/attention. Wash skin with plenty of water. Take off contaminated clothing. If skin irritation occurs: Get medical advice/attention.

First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to

do. Continue rinsing. Immediately call a poison center or doctor/physician. Call a physician

immediately.

First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention. Call a poison

center/doctor/physician if you feel unwell.

4.2. Most important symptoms and effects (acute and delayed)

Potential Adverse human health effects and : Based or

symptoms

: Based on available data, the classification criteria are not met.

Symptoms/injuries after skin contact : Causes skin irritation. Irritation.

Symptoms/injuries after eye contact : Causes serious eye damage. Serious damage to eyes.

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Water spray. Sand.

Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Specific hazards arising from the chemical

Hazardous decomposition products in case of : Toxic fumes may be released.

fire

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any

chemical fire. Prevent fire-fighting water from entering environment.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection. Do

not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. Evacuate unnecessary personnel. Avoid contact with skin and eyes.

05/27/2020 EN (English US) 2/10

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. Equip cleanup crew with

proper protection. For further information refer to section 8: "Exposure controls/personal

protection".

Emergency procedures : Ventilate area.

6.2. Environmental precautions

Avoid release to the environment. See Section 12 for additional Ecological information.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material. Soak up spills with inert solids, such as clay or

diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.

Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection. For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good

soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor. Avoid contact with skin and eyes.

Wear personal protective equipment.

Hygiene measures : Wash hands and other exposed skin thoroughly after handling. Wash contaminated clothing

before reuse. Do not eat, drink or smoke when using this product. Always wash hands after

handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep only in the original container in a cool, well ventilated place away from : Direct sunlight,

Heat sources. Keep container closed when not in use. Store in a well-ventilated place. Keep

cool.

Incompatible products : Strong acids. Oxidizing agent.

Incompatible materials : Sources of ignition. Direct sunlight.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

ACGIH TWA (ppm)

ACGIH STEL (ppm)

USA - OSHA - Occupational Exposure Limits

Remark (ACGIH)

Local name

PREVAIL		
No additional information available		
UNDECETH-5 (34398-01-1)		
No additional information available		
butyl glycolether (111-76-2)		
USA - ACGIH - Occupational Exposure Limits		
Local name	2-Butoxyethanol (EGBE)	
ACGIH TWA (ppm)	20 ppm	
Remark (ACGIH)	Eye & URT irr	
USA - OSHA - Occupational Exposure Limits		
Local name	2-Butoxyethanol	
OSHA PEL (TWA) (mg/m³)	240 mg/m³	
OSHA PEL (TWA) (ppm)	50 ppm	
Tetrasodium ethylenediaminetetraactetate (64-02-8)		
No additional information available		
Ethanolamine (141-43-5)		
USA - ACGIH - Occupational Exposure Limits		
Local name	Ethanolamine	

05/27/2020 EN (English US) 3/10

3 ppm

6 ppm

Eye & skin irr

Ethanolamine

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

OSHA PEL (TWA) (mg/m³)	6 mg/m³
OSHA PEL (TWA) (ppm)	3 ppm

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.

Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Avoid all unnecessary exposure.

Hand protection:

Wear protective gloves

Eye protection:

Chemical goggles or safety glasses. Safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

Wear appropriate mask

Personal protective equipment symbol(s):



Other information:

Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid
Color : Blue
Odor : Detergent

Odor threshold : No data available

pH : 11 pH solution : 1 %

Melting point: Not applicableFreezing point: No data availableBoiling point: No data available

Flash point : > 212 °F

Relative evaporation rate (butyl acetate=1) : No data available Flammability (solid, gas) : Non flammable. Vapor pressure : No data available Relative vapor density at 20 °C : No data available

Relative density : 1 – 1.01

Specific gravity / density : 8.40 lb/gal

Solubility : Soluble in water.

Partition coefficient n-octanol/water (Log Pow) : No data available

Auto-ignition temperature : No data available

Decomposition temperature : No data available

05/27/2020 EN (English US) 4/10

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Viscosity, kinematic : No data available Viscosity, dynamic : No data available **Explosion limits** : No data available Explosive properties : No data available Oxidizing properties : No data available

9.2. Other information

VOC content : 5.5 %

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Not established.

Conditions to avoid 10.4.

Direct sunlight. Extremely high or low temperatures.

Incompatible materials

UNDECETH-5 (34398-01-1)

Strong acids. Oxidizing agent.

10.6. **Hazardous decomposition products**

fume. Carbon monoxide. Carbon dioxide.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified Acute toxicity (dermal) : Not classified : Not classified Acute toxicity (inhalation)

LD50 oral rat	> 1400 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
butyl glycolether (111-76-2)	
LD50 oral rat	1746 mg/kg body weight (Equivalent or similar to OECD 401, Rat, Male, Experimental value, Oral)
LD50 dermal rat	> 2000 mg/kg body weight (Rat; Experimental value; OECD 402: Acute Dermal Toxicity)
LD50 dermal rabbit	435 mg/kg body weight (Rabbit; Experimental value; OECD 402: Acute Dermal Toxicity; 435 mg/kg bodyweight; Rabbit; Weight of evidence; Equivalent or similar to OECD 402)
LC50 inhalation rat (ppm)	450-486,Rat; Weight of evidence

Tetrasodium ethylenediaminetetraactetate (64-02-8)	
LD50 oral rat	> 2000 mg/kg (Rat, Oral)
LD50 dermal rabbit	> 5000 mg/kg
LC50 inhalation rat (mg/l)	4.14 mg/l/4h Dust

Ethanolamine (141-43-5)	
LD50 oral rat	1515 mg/kg body weight (Equivalent or similar to OECD 401, Rat, Male / female, Experimental value, Oral, 7 day(s))
LD50 dermal rabbit	2504 – 2881 mg/kg body weight (Equivalent or similar to OECD 402, 24 week(s), Rabbit, Male / female, Experimental value, Dermal)

Skin corrosion/irritation : Causes skin irritation.

pH: 11

Serious eye damage/irritation : Causes serious eye damage.

pH: 11

: Not classified Respiratory or skin sensitization Germ cell mutagenicity : Not classified

05/27/2020 EN (English US) 5/10

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Carcinogenicity : Not classified

Reproductive toxicity : Not classified

Specific target organ toxicity – single exposure : Not classified

Specific target organ toxicity - repeated

exposure

: Not classified

Aspiration hazard : Not classified
Viscosity, kinematic : No data available

Potential Adverse human health effects and

symptoms

: Based on available data, the classification criteria are not met.

Symptoms/injuries after skin contact : Causes skin irritation. Irritation.

Symptoms/injuries after eye contact : Causes serious eye damage. Serious damage to eyes.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms or to cause long-term adverse

effects in the environment.

UNDECETH-5 (34398-01-1)	
LC50 fish 1	1 – 10 mg/l (96 hr.)
EC50 Daphnia 1	1 – 10 mg/l (48 hr.)
EC50 other aquatic organisms 1	1 – 10 mg/l (96 hr.)(Algae)

butyl glycolether (111-76-2)	
LC50 fish 1	1474 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Oncorhynchus mykiss, Static system, Fresh water, Experimental value, Nominal concentration)
EC50 Daphnia 1	1550 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, Nominal concentration)
ErC50 (algae)	911 mg/l (72 Hr.)

Tetrasodium ethylenediaminetetraactetate (64-02-8)		
LC50 fish 1	121 mg/l (96 h, Lepomis macrochirus, Literature study, Soft water)	
EC50 Daphnia 1	625 mg/l (24 h, Daphnia magna, Literature study)	
Ethanolamine (141-43-5)		
LC50 fish 1	349 mg/l (EU Method C.1, 96 h, Cyprinus carpio, Semi-static system, Fresh water, Experimental value, GLP)	

	Experimental value, GLP)
EC50 Daphnia 1	65 mg/l (EU Method C.2, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, GLP)

12.2. Persistence and degradability

PREVAIL		
Persistence and degradability	Not established.	
butyl glycolether (111-76-2)		
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. Photodegradation in the air.	
Biochemical oxygen demand (BOD)	0.71 g O₂/g substance	
Chemical oxygen demand (COD)	2.2 g O₂/g substance	
ThOD	2.305 g O₂/g substance	
BOD (% of ThOD)	0.31	
Tetrasodium ethylenediaminetetraactetate (64-02-8)		
Persistence and degradability	Not readily biodegradable in water.	

Persistence and degradability	Not readily biodegradable in water.
Biochemical oxygen demand (BOD)	< 0.002 g O₂/g substance
Chemical oxygen demand (COD)	0.54 – 0.58 g O₂/g substance

05/27/2020 EN (English US) 6/10

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Ethanolamine (141-43-5)	
Persistence and degradability	Biodegradable in the soil. Readily biodegradable in water.
Biochemical oxygen demand (BOD)	0.8 g O₂/g substance
Chemical oxygen demand (COD)	1.34 g O₂/g substance
ThOD	2.49 g O₂/g substance
BOD (% of ThOD)	0.32

12.3. Bioaccumulative potential

PREVAIL		
Bioaccumulative potential	Not established.	
butyl glycolether (111-76-2)		
Partition coefficient n-octanol/water (Log Pow)	0.81 (Experimental value; BASF test; 25 °C)	
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).	
Tetrasodium ethylenediaminetetraactetate (64-02-8)		
Partition coefficient n-octanol/water (Log Pow)	-2.6	
Bioaccumulative potential	Not bioaccumulative.	
Ethanolamine (141-43-5)		
BCF other aquatic organisms 1	2.3 – 9.2 (BCFWIN, Calculated value)	
Partition coefficient n-octanol/water (Log Pow)	-2.3 (Experimental value, OECD 107: Partition Coefficient (n-octanol/water): Shake Flask Method, 25 °C)	
Bioaccumulative potential	Not bioaccumulative.	

12.4. Mobility in soil

utyl glycolether (111-76-2)	
Surface tension	0.027 N/m (25 °C)
Ecology - soil	Low potential for adsorption in soil.
Ethanolamine (141-43-5)	
Surface tension	No data available in the literature
Partition coefficient n-octanol/water (Log Koc)	1.16 (log Koc, Calculated value)
Ecology - soil	Highly mobile in soil.

12.5. Other adverse effects

Other information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Disposal methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.

Ecology - waste materials : Avoid release to the environment.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Other information : No supplementary information available.

Transportation of Dangerous Goods

Transport by sea

Air transport

05/27/2020 EN (English US) 7/10

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory except for:

di(tetramethylammonium)(29H,31H-phthalocyanin-	CAS-No. 12222-04-7	< 0.1%
N29,N30,N31,N32)disulfonamide disulfonate, cuprate(2-		
)complex, derivates		

Contains chemical(s) subject to TSCA 12b export notification if product is shipped outside the U.S

	· / /	<u> </u>		
Acetaldehyde			CAS-No. 75-07-0	< 0.1%
Chamical(a) aubi	ant to the reporting require	monto of Cootion 212 or	Title III of the Cunorfund Amendm	anto and Deputherization Act (CADA) of

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

Ethylene oxide	CAS-No. 75-21-8	< 0.1%
Acetaldehyde	CAS-No. 75-07-0	< 0.1%
ethylene glycol	CAS-No. 107-21-1	< 0.1%
Diethanolamine	CAS-No. 111-42-2	< 0.1%

UNDECETH-5 (34398-01-1)	
EPA TSCA Regulatory Flag	N - N - indicates a polymeric substance containing no free-radical initiator in its Inventory name but is considered to cover the designated polymer made with any free-radical initiator regardless of the amount used. P - P - indicates a commenced PMN substance. XU - XU - indicates a substance exempt from reporting under the Inventory Update Reporting Rule, i.e, Partial Updating of the TSCA Inventory Data Base Production and Site Reports (40 CFR 710(C)).
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard

Ethylene oxide (75-21-8)	
Listed on EPA Hazardous Air Pollutant (HAPS)	
CERCLA RQ	10 lb
RQ (Reportable quantity, section 304 of EPA's List of Lists)	10 lb
SARA Section 302 Threshold Planning Quantity (TPQ)	1000 lb

Acetaldehyde (75-07-0)		
Listed on EPA Hazardous Air Pollutant (HAPS)		
EPA TSCA Regulatory Flag	T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA.	
CERCLA RQ	1000 lb	

butyl glycolether (111-76-2)	
SARA Section 311/312 Hazard Classes	Fire hazard Immediate (acute) health hazard
	Delayed (chronic) health hazard

ethylene glycol (107-21-1)	
Listed on EPA Hazardous Air Pollutant (HAPS)	
CERCLA RO	5000 lb

	l etrasodium etnylenediaminetetraactetate (64-02-8)	
	SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard
Sodium hydroxide (1310-73-2) CERCLA RQ 1000 lb		
		1000 lb

CERCLA RQ	1000 lb
Diethanolamine (111-42-2)	
Listed on EPA Hazardous Air Pollutant (HAPS)	
CERCLA RQ	100 lb

15.2. International regulations

	Ethylene oxide (75-21-8)	
Listed on IARC (International Agency for Research on Cancer)		
	Listed as carcinogen on NTP (National Toxicology Program)	

05/27/2020 EN (English US) 8/10

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Acetaldehyde (75-07-0)

Listed as carcinogen on NTP (National Toxicology Program)

Diethanolamine (111-42-2)

Listed on IARC (International Agency for Research on Cancer)

15.3. US State regulations



This product can expose you to Ethylene oxide, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Component	State or local regulations
Ethylene oxide(75-21-8)	U.S New Jersey - Right to Know Hazardous Substance List
Acetaldehyde(75-07-0)	U.S New Jersey - Right to Know Hazardous Substance List
Glycerol(56-81-5)	U.S New Jersey - Right to Know Hazardous Substance List
butyl glycolether(111-76-2)	U.S New Jersey - Right to Know Hazardous Substance List
ethylene glycol(107-21-1)	U.S New Jersey - Right to Know Hazardous Substance List
Sodium hydroxide(1310-73-2)	U.S New Jersey - Right to Know Hazardous Substance List
Ethanolamine(141-43-5)	U.S New Jersey - Right to Know Hazardous Substance List
Diethanolamine(111-42-2)	U.S New Jersey - Right to Know Hazardous Substance List

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date : 05/27/2020
Other information : None.

05/27/2020 EN (English US) 9/10

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full text of H-phrases:

Acute Tox. 3 (Dermal)	Acute toxicity (dermal) Category 3
Acute Tox. 4 (Inhalation)	Acute toxicity (inhalation) Category 4
Acute Tox. 4 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4
Aquatic Acute 3	Hazardous to the aquatic environment - Acute Hazard Category 3
Eye Dam. 1	Serious eye damage/eye irritation Category 1
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Eye Irrit. 2B	Serious eye damage/eye irritation Category 2B
Flam. Liq. 4	Flammable liquids Category 4
Skin Corr. 1	Skin corrosion/irritation Category 1
Skin Irrit. 2	Skin corrosion/irritation Category 2
H227	Combustible liquid
H302	Harmful if swallowed
H311	Toxic in contact with skin
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H318	Causes serious eye damage
H319	Causes serious eye irritation
H320	Causes eye irritation
H332	Harmful if inhaled
H402	Harmful to aquatic life

SDS US (GHS HazCom 2012)

The information provided on this document is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

05/27/2020 EN (English US) 10/10