

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Version: 1.0

Date of issue: 09/17/2013 Revision date: 05/14/2020 Supersedes: 02/27/2014

SECTION 1: Identification

1.1. Identification

Product form : Mixture

Product name : OLD YELLER DEGREASER

Product code : OLDY

1.2. Recommended use and restrictions on use

Use of the substance/mixture : Industrial and Institutional Alkaline Degreaser

1.3. Supplier

Sky Blue Industries, Inc. 760 W. Exchange Road Ogden, Utah 84401 - USA T (800) 998-2808

www.skyblueindustries.com

1.4. Emergency telephone number

Emergency number : Chemtrec 1-800-424-9300

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Skin Irrit. 2 H315 Causes skin irritation
Eye Dam. 1 H318 Causes serious eye damage

Full text of hazard classes and H-statements : see section 16

2.2. GHS Label elements, including precautionary statements

GHS US labeling

Hazard pictograms (GHS-US)



Signal word (GHS-US) : Danger

Hazard statements (GHS-US) : H315 - Causes skin irritation

H318 - Causes serious eye damage

Precautionary statements (GHS-US) : P264 - Wash hands, forearms and face thoroughly after handling

P280 - Wear protective gloves/protective clothing/eye protection/face protection

P302+P352 - If on skin: Wash with plenty of water/...

P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing P310 - Immediately call a poison center/doctor/... P321 - Specific treatment (see ... on this label)

P332+P313 - If skin irritation occurs: Get medical advice/attention P362+P364 - Take off contaminated clothing and wash it before reuse

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

05/14/2020 EN (English US) Page 1

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Name	Product identifier	%	GHS US classification
butyl glycolether	(CAS-No.) 111-76-2	5 – 10	Flam. Liq. 4, H227 Acute Tox. 4 (Oral), H302 Acute Tox. 3 (Dermal), H311 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2B, H320
Tetrasodium ethylenediaminetetraactetate	(CAS-No.) 64-02-8	1 – 3	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Inhalation:dust,mist), H332 Eye Dam. 1, H318
Ethanolamine	(CAS-No.) 141-43-5	1 – 3	Flam. Liq. 4, H227 Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Inhalation), H332 Skin Corr. 1, H314 Aquatic Acute 3, H402
UNDECETH-5	(CAS-No.) 34398-01-1	1 – 3	Skin Irrit. 2, H315 Eye Irrit. 2A, H319
Sodium hydroxide	(CAS-No.) 1310-73-2	1 – 3	Met. Corr. 1, H290 Skin Corr. 1, H314 Aquatic Acute 3, H402

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. **Description of first aid measures**

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.

Wash skin with plenty of water. Take off contaminated clothing. If skin irritation occurs: Get First-aid measures after skin contact

medical advice/attention.

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to First-aid measures after eye contact

do. Continue rinsing. Call a physician immediately.

First-aid measures after ingestion : Call a poison center/doctor/physician if you feel unwell.

Most important symptoms and effects (acute and delayed)

: Irritation. Symptoms/injuries after skin contact

Symptoms/injuries after eye contact : Serious damage to eyes

Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

5.2. Specific hazards arising from the chemical

Hazardous decomposition products in case of : Toxic fumes may be released.

fire

5.3. Special protective equipment and precautions for fire-fighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing

apparatus. Complete protective clothing

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Emergency procedures : Ventilate spillage area. Avoid contact with skin and eyes.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information

refer to section 8: "Exposure controls/personal protection".

6.2. **Environmental precautions**

Avoid release to the environment.

Methods and material for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material.

Other information : Dispose of materials or solid residues at an authorized site.

05/14/2020 EN (English US) 2/10

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Avoid contact with skin and eyes. Wear personal

protective equipment.

Hygiene measures : Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product.

Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in a well-ventilated place. Keep cool.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

OLD YELLER DEGREASER	
No additional information available	
Sodium hydroxide (1310-73-2)	
USA - ACGIH - Occupational Exposure Limits	
Local name	Sodium hydroxide
ACGIH Ceiling (mg/m³)	2 mg/m³
Remark (ACGIH)	URT, eye, & skin irr
USA - OSHA - Occupational Exposure Limits	
Local name	Sodium hydroxide
OSHA PEL (TWA) (mg/m³)	2 mg/m³
butyl glycolether (111-76-2)	
USA - ACGIH - Occupational Exposure Limits	
Local name	2-Butoxyethanol (EGBE)
ACGIH TWA (ppm)	20 ppm
Remark (ACGIH)	Eye & URT irr
USA - OSHA - Occupational Exposure Limits	
Local name	2-Butoxyethanol
OSHA PEL (TWA) (mg/m³)	240 mg/m³
OSHA PEL (TWA) (ppm)	50 ppm
Ethanolamine (141-43-5)	
USA - ACGIH - Occupational Exposure Limits	
Local name	Ethanolamine
ACGIH TWA (ppm)	3 ppm
ACGIH STEL (ppm)	6 ppm
Remark (ACGIH)	Eye & skin irr
USA - OSHA - Occupational Exposure Limits	
Local name	Ethanolamine
OSHA PEL (TWA) (mg/m³)	6 mg/m³
OSHA PEL (TWA) (ppm)	3 ppm
UNDECETH-5 (34398-01-1)	
No additional information available	
Tetrasodium ethylenediaminetetraactetate (64-02-8)	
No additional information available	

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.

Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

05/14/2020 EN (English US) 3/10

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Hand protection:

Protective gloves

Eye protection:

Safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

Personal protective equipment symbol(s):



SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid

Color : No data available
Odor : No data available
Odor threshold : No data available

pH : > 11

Melting point: Not applicableFreezing point: No data availableBoiling point: No data available

Flash point : > 212 °F

Relative evaporation rate (butyl acetate=1) : No data available Flammability (solid, gas) : Not applicable. Vapor pressure : No data available Relative vapor density at 20 °C : No data available

Relative density : 1.02 Specific gravity / density : 8.52 lb/gal Solubility : No data available Partition coefficient n-octanol/water (Log Pow) No data available : No data available Auto-ignition temperature Decomposition temperature : No data available : No data available Viscosity, kinematic Viscosity, dynamic : No data available **Explosion limits** : No data available Explosive properties No data available Oxidizing properties : No data available

9.2. Other information

VOC content : 10.1 %

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

05/14/2020 EN (English US) 4/10

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

butyl glycolether (111-76-2)	
LD50 oral rat	1746 mg/kg body weight (Equivalent or similar to OECD 401, Rat, Male, Experimental value, Oral)
LD50 dermal rat	> 2000 mg/kg body weight (Rat; Experimental value; OECD 402: Acute Dermal Toxicity)
LD50 dermal rabbit	435 mg/kg body weight (Rabbit; Experimental value; OECD 402: Acute Dermal Toxicity; 435 mg/kg bodyweight; Rabbit; Weight of evidence; Equivalent or similar to OECD 402)
LC50 inhalation rat (ppm)	450-486,Rat; Weight of evidence
Ethanolamine (141-43-5)	

Ethanolamine (141-43-5)	
LD50 oral rat	1515 mg/kg body weight (Equivalent or similar to OECD 401, Rat, Male / female, Experimental value, Oral, 7 day(s))
LD50 dermal rabbit	2504 – 2881 mg/kg body weight (Equivalent or similar to OECD 402, 24 week(s), Rabbit, Male / female. Experimental value. Dermal)

UNDECETH-5 (34398-01-1)		
LD50 oral rat	> 1400 mg/kg	
LD50 dermal rabbit	> 2000 mg/kg	

Tetrasodium ethylenediaminetetraactetate (64-02-8)	
LD50 oral rat	> 2000 mg/kg (Rat, Oral)
LD50 dermal rabbit	> 5000 mg/kg
LC50 inhalation rat (mg/l)	4.14 mg/l/4h Dust

Skin corrosion/irritation : Causes skin irritation.

pH: > 11

Serious eye damage/irritation : Causes serious eye damage.

pH: > 11

Respiratory or skin sensitization : Not classified Germ cell mutagenicity : Not classified Carcinogenicity : Not classified

Reproductive toxicity : Not classified

Specific target organ toxicity – single exposure : Not classified

Specific target organ toxicity – repeated

exposure

: Not classified

Aspiration hazard : Not classified
Viscosity, kinematic : No data available

Symptoms/injuries after skin contact : Irritation.

05/14/2020 EN (English US) 5/10

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Symptoms/injuries after eye contact : Serious damage to eyes.

SECTION 12: Ecological information

12.1. Toxic	JΙ	٧

Ecology - general : The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment.

	enects in the environment.
Sodium hydroxide (1310-73-2)	
LC50 fish 1	45.4 mg/l (96 h, Salmo gairdneri, Static system, Fresh water, Experimental value, Solution >=50%)
EC50 Daphnia 1	40.4 mg/l (48 h, Ceriodaphnia sp., Experimental value, Nominal concentration)
butyl glycolether (111-76-2)	
LC50 fish 1	1474 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Oncorhynchus mykiss, Static system, Fresh water, Experimental value, Nominal concentration)
EC50 Daphnia 1	1550 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, Nominal concentration)
ErC50 (algae)	911 mg/l (72 Hr.)
Ethanolamine (141-43-5)	
LC50 fish 1	349 mg/l (EU Method C.1, 96 h, Cyprinus carpio, Semi-static system, Fresh water, Experimental value, GLP)
EC50 Daphnia 1	65 mg/l (EU Method C.2, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, GLP)
UNDECETH-5 (34398-01-1)	
LC50 fish 1	1 – 10 mg/l (96 hr.)
EC50 Daphnia 1	1 – 10 mg/l (48 hr.)
EC50 other aquatic organisms 1	1 – 10 mg/l (96 hr.)(Algae)
Tetrasodium ethylenediaminetetraactetate (64-02-8)	
LC50 fish 1	121 mg/l (96 h, Lepomis macrochirus, Literature study, Soft water)
EC50 Daphnia 1	625 mg/l (24 h, Daphnia magna, Literature study)

12.2. Persistence and degradability

Persistence and degradability

Sodium hydroxide (1310-73-2)			
Persistence and degradability	Biodegradability: not applicable.		
Chemical oxygen demand (COD)	Not applicable (inorganic)		
ThOD	Not applicable (inorganic)		
butyl glycolether (111-76-2)			
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. Photodegradation in the air.		
Biochemical oxygen demand (BOD)	0.71 g O₂/g substance		
Chemical oxygen demand (COD)	2.2 g O₂/g substance		
ThOD	2.305 g O₂/g substance		
BOD (% of ThOD)	0.31		
Ethanolamine (141-43-5)	Ethanolamine (141-43-5)		
Persistence and degradability	Biodegradable in the soil. Readily biodegradable in water.		
Biochemical oxygen demand (BOD)	0.8 g O₂/g substance		
Chemical oxygen demand (COD)	1.34 g O₂/g substance		
ThOD	2.49 g O₂/g substance		
BOD (% of ThOD)	0.32		
Tetrasodium ethylenediaminetetraactetate (64-02-8)			

Biochemical oxygen demand (BOD)	< 0.002 g O₂/g substance
Chemical oxygen demand (COD)	0.54 – 0.58 g O₂/g substance

Not readily biodegradable in water.

05/14/2020 EN (English US) 6/10

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

12.3. Bioaccumulative potential

Sodium hydroxide (1310-73-2)		
Bioaccumulative potential	Not bioaccumulative.	
butyl glycolether (111-76-2)		
Partition coefficient n-octanol/water (Log Pow)	0.81 (Experimental value; BASF test; 25 °C)	
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).	
Ethanolamine (141-43-5)		
BCF other aquatic organisms 1	2.3 – 9.2 (BCFWIN, Calculated value)	
Partition coefficient n-octanol/water (Log Pow)	-2.3 (Experimental value, OECD 107: Partition Coefficient (n-octanol/water): Shake Flask Method, 25 °C)	
Bioaccumulative potential	Not bioaccumulative.	
Tetrasodium ethylenediaminetetraactetate (64-02-8)		
Partition coefficient n-octanol/water (Log Pow)	-2.6	
Bioaccumulative potential	Not bioaccumulative.	

12.4. Mobility in soil

Sodium hydroxide (1310-73-2)		
Ecology - soil	No (test)data on mobility of the substance available.	
butyl glycolether (111-76-2)		
Surface tension	0.027 N/m (25 °C)	
Ecology - soil	Low potential for adsorption in soil.	
Ethanolamine (141-43-5)		
Surface tension	No data available in the literature	
Partition coefficient n-octanol/water (Log Koc)	1.16 (log Koc, Calculated value)	
Ecology - soil	Highly mobile in soil.	

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Disposal methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Not applicable

Transportation of Dangerous Goods

Not applicable

Transport by sea

Not applicable

Air transport

Not applicable

SECTION 15: Regulatory information

15.1. US Federal regulations

05/14/2020 EN (English US) 7/10

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

Contains chemical(s) subject to TSCA 12b export notification if product is shipped outside the U.S

Contains chemical(s) subject to 130A 12b expor	i notineation ii product is shipped odiside the 0.5	
Acetaldehyde	CAS-No. 75-07-0	< 0.1%
Chemical(s) subject to the reporting requirements 1986 and 40 CFR Part 372.	s of Section 313 or Title III of the Superfund Amer	ndments and Reauthorization Act (SARA) of
Methyl alcohol	CAS-No. 67-56-1	< 0.1%
ethylene glycol	CAS-No. 107-21-1	< 0.1%
Diethanolamine	CAS-No. 111-42-2	< 0.1%
Ethylene oxide	CAS-No. 75-21-8	< 0.1%
Acetaldehyde	CAS-No. 75-07-0	< 0.1%
Sodium hydroxide (1310-73-2)		
CERCLA RQ	1000 lb	
Sodium tripolyphosphate (7758-29-4)		
CERCLA RQ	5000 lb	
Methyl alcohol (67-56-1)		
Listed on EPA Hazardous Air Pollutant (HAPS)		
CERCLA RQ	5000 lb	
butyl glycolether (111-76-2)	Fire hererd	
SARA Section 311/312 Hazard Classes	Fire hazard Immediate (acute) health hazard Delayed (chronic) health hazard	
ethylene glycol (107-21-1)		
Listed on EPA Hazardous Air Pollutant (HAPS)		
CERCLA RQ	5000 lb	
Diethanolamine (111-42-2)		
Listed on EPA Hazardous Air Pollutant (HAPS)		
CERCLA RQ	100 lb	
UNDECETH-5 (34398-01-1)		
EPA TSCA Regulatory Flag	N - N - indicates a polymeric substance containing no free-radical initiator in its Inventory name but is considered to cover the designated polymer made with any free-radical initiator regardless of the amount used. P - P - indicates a commenced PMN substance. XU - XU - indicates a substance exempt from reporting under the Inventory Update Reporting Rule, i.e, Partial Updating of the TSCA Inventory Data Base Production and Site Reports (40 CFR 710(C)).	
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard	
Ethylene oxide (75-21-8)		
Listed on EPA Hazardous Air Pollutant (HAPS)		
CERCLA RQ	10 lb	
RQ (Reportable quantity, section 304 of EPA's List of Lists)	10 lb	
SARA Section 302 Threshold Planning Quantity (TPQ)	1000 lb	
Acetaldehyde (75-07-0)		
Listed on EPA Hazardous Air Pollutant (HAPS)		
EPA TSCA Regulatory Flag	T - T - indicates a substance that is the subject	of a Section 4 test rule under TSCA.
CERCLA RQ	1000 lb	
Tetrasodium ethylenediaminetetraactetate (64	I-02-8)	

15.2. International regulations

05/14/2020 EN (English US) 8/10

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Diethanolamine (111-42-2)

Listed on IARC (International Agency for Research on Cancer)

Ethylene oxide (75-21-8)

Listed on IARC (International Agency for Research on Cancer) Listed as carcinogen on NTP (National Toxicology Program)

Acetaldehyde (75-07-0)

Listed as carcinogen on NTP (National Toxicology Program)

15.3. US State regulations



This product can expose you to Ethylene oxide, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Component	State or local regulations
Sodium hydroxide(1310-73-2)	U.S New Jersey - Right to Know Hazardous Substance List
butyl glycolether(111-76-2)	U.S New Jersey - Right to Know Hazardous Substance List
ethylene glycol(107-21-1)	U.S New Jersey - Right to Know Hazardous Substance List
Ethanolamine(141-43-5)	U.S New Jersey - Right to Know Hazardous Substance List
Diethanolamine(111-42-2)	U.S New Jersey - Right to Know Hazardous Substance List
Ethylene oxide(75-21-8)	U.S New Jersey - Right to Know Hazardous Substance List
Acetaldehyde(75-07-0)	U.S New Jersey - Right to Know Hazardous Substance List
Methyl alcohol(67-56-1)	U.S New Jersey - Right to Know Hazardous Substance List

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date : 05/14/2020

05/14/2020 EN (English US) 9/10

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full text of H-phrases:

Acute Tox. 3 (Dermal)	Acute toxicity (dermal) Category 3
Acute Tox. 4 (Inhalation)	Acute toxicity (inhalation) Category 4
Acute Tox. 4 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4
Aquatic Acute 3	Hazardous to the aquatic environment - Acute Hazard Category 3
Eye Dam. 1	Serious eye damage/eye irritation Category 1
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Eye Irrit. 2B	Serious eye damage/eye irritation Category 2B
Flam. Liq. 4	Flammable liquids Category 4
Met. Corr. 1	Corrosive to metals Category 1
Skin Corr. 1	Skin corrosion/irritation Category 1
Skin Irrit. 2	Skin corrosion/irritation Category 2
H227	Combustible liquid
H290	May be corrosive to metals
H302	Harmful if swallowed
H311	Toxic in contact with skin
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H318	Causes serious eye damage
H319	Causes serious eye irritation
H320	Causes eye irritation
H332	Harmful if inhaled
H402	Harmful to aquatic life

SDS US (GHS HazCom 2012)

The information provided on this document is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

05/14/2020 EN (English US) 10/10